

Heat Storage Webinar Series Pt. 2: HT-Borehole Thermal Energy Storage


System Integration Aspects

30. November 2023
Julian Formhals
Vattenfall Wärme Berlin
System Development | Network Planning
Confidentiality: C1 - Public




VATTENFALL

How are HT-BTES typically integrated into DH systems




Storage efficiency


Storage efficiency is not as important as system efficiency



Welsch et al. 2016





Welsch et al. 2016



Case Study – Grid Temperatures

How do grid temperatures affect storage performance?






- Fixed system design and control strategy
- Heat pump power adapted to temperature shift
- Simulation over 8 years

Case Study – Grid Temperatures

Looking at storage efficiency alone does not show the whole story

■	F: 80 °C – 110 °C; R: 60 °C
■	F: 70 °C – 93 °C; R: 50 °C
■	F: 60 °C – 77 °C; R: 40 °C
■	F: 50 °C – 60 °C; R: 30 °C



(Formhals et al. 2017)

HT-BTES in DH

Integration of a medium deep HT-BTES into the TU Darmstadt DH grid




Institute for Sustainable Building Design, TU Darmstadt, 2020.

Project: SKEWS, TU Darmstadt, Geothermal Science & Technology

Case study – transition strategies


Transition to HT-BTES and Solar Thermal – When and how much



Formhals et al. (2021)

Case study – transition strategies

Time of construction and size should follow efficiency measures of the DH grid



Emission target
øEF 2025-2050


- Reference: status quo system
- Immediate: construction in 2025
- Conservative: low speed and small size
- Step: construction in 2030
- Progressive: maximum system in 2030
- Gradual: gradual construction

Recommended strategy: Gradual/42,000 m² solar & 37 BHEs

	2025	2030	2040
Solar	14,000 m ²	28,000 m ²	42,000 m ²
BTES	-	19 BHEs	37 BHEs
CHP	3 MW _{th}	1,5 MW _{th}	0,5 MW _{th}
HPC cooling	HP→ret	HP→sup	dir→sup


Case Study – Groundwater Flow

Is HT-BTES possible in regions with groundwater flow?



BTES

- 18 BHEs of 100 m
- 3 BHEs connected in series



Hydrogeology


- Hydraulic gradient:
0.01 m/m
- Hydr. conductivity:
10⁻⁸ – 10⁻⁴ m/s

Formhals et al. (2022)


Case Study – Groundwater Flow

Flowing groundwater transports the heat out of the storage region


$k_f = 10^{-8} \text{ m/s}$
→ 3.2 mm/a



$k_f = 10^{-4} \text{ m/s}$
→ 32 m/a




Strong groundwater flow reduces storage performance and heat pump COP




Brødstrup DH

Brødstrup Solar DH system with HT-BTES



(Arcon-Sunmark, 2017)

Brødstrup Fjernvarme supplies around 1,500 households with 37-42 GWh/a



(Solites, 2019)


Usefulness of seasonal storage is highly dependant of the overall system and availability of excess heat

Storage energy turnover for 2014-2017



- Storage efficiency of 74,4% in average
- Annual charging of 192 MWh
- Much lower than design number of 510 MWh
- Increased heat demand resulted in no solar excess during summer
- The seasonal storage was hardly used

Heat supply (broad) vs demand (thin)




Key take aways

- HT-BTES can store very large amounts of heat for reasonable storage costs
- Very high efficiencies are possible - even above 100%
- ...but the integration into the system and temperature levels defines the overall efficiency
- A good combination is to have high temperature heat sources for storage (75-90 °C) and low grid temperatures (ideally 80 °C or lower)
- Significant groundwater flow reduces storage and system efficiency
- Storage performance and usefulness is highly dependant on the overall system (availability and temperature of excess heat, grid temperatures,...)

**Bedankt voor
jullie aandacht**

Questions?

**Contact:
julian.formhals@vattenfall.de**



References

- Formhals et al. 2017:** Effects of the District Heating Supply Temperature on the Efficiency of Borehole Thermal Energy Storage Systems, Proceedings 3rd International Conference on Smart Energy Systems and 4th Generation District Heating, Copenhagen, Denmark, 12-13 September 2017, <http://tubiblio.ulb.tu-darmstadt.de/89333/>.
- Formhals et al. 2021:** Strategies towards a transition towards a solar district heating grid with integrated seasonal geothermal storage, TU Darmstadt, Geothermal Science and Technology, Elsevier, Energy, <https://doi.org/10.1016/j.energy.2021.120662>.
- Formhals et al. 2022:** Co-Simulation of District Heating Systems and Borehole Heat Exchanger Arrays using 3D Finite Element Method Subsurface Models, TU Darmstadt, Geothermal Science and Technology, Journal of Building Performance Simulation, Taylor & Francis, <https://doi.org/10.1080/19401493.2022.2058088>.
- Schmidt 2019:** Brædstrup District Heating monitoring data evaluation for the years 2014-2017, Solites.
- Welsch et al. 2016:** Characteristics of medium deep borehole thermal energy storage, TU Darmstadt, Geothermal Science and Technology, International Journal of Energy Research, Wiley, <https://doi.org/10.1002/er.3570>.